# **Material Safety Data Sheet**

Version 4.1 Revision Date 03/18/2011 Print Date 04/03/2011

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : 2-Propanol

Product Number : 19516 Brand : Sigma

Supplier : Sigma-Aldrich

3050 Spruce Street SAINT LOUIS MO 63103

USA

Telephone : +1 800-325-5832 Fax : +1 800-325-5052 Emergency Phone # (For : (314) 776-6555

both supplier and manufacturer)

Preparation Information

Sigma-Aldrich Corporation

Product Safety - Americas Region

1-800-521-8956

# 2. HAZARDS IDENTIFICATION

# **Emergency Overview**

# **OSHA Hazards**

Flammable liquid, Target Organ Effect, Irritant

# **Target Organs**

Gastrointestinal tract, Liver, Cardiovascular system., Kidney, Nerves.

#### **GHS Classification**

Flammable liquids (Category 2) Skin irritation (Category 3) Eye irritation (Category 2A)

Specific target organ toxicity - single exposure (Category 3)

# GHS Label elements, including precautionary statements

Pictogram



Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.

H316 Causes mild skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

**HMIS Classification** 

Health hazard: 2 Chronic Health Hazard: \* Flammability: 3 Physical hazards: 0 Reactivity: 1

**NFPA Rating** 

Health hazard: 2 Fire: 3 Reactivity Hazard: 1

# **Potential Health Effects**

**Inhalation** May be harmful if inhaled. Causes respiratory tract irritation. Vapours may cause

drowsiness and dizziness.

**Skin** May be harmful if absorbed through skin. Causes skin irritation.

**Eyes** Causes eye irritation.

**Ingestion** May be harmful if swallowed.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms : sec-Propyl alcohol

Isopropyl alcohol Isopropanol

Formula : C<sub>3</sub>H<sub>8</sub>O Molecular Weight : 60.1 g/mol

CAS-No.	EC-No. Index-No. Concentration		Concentration
2-Propanol			
67-63-0	200-661-7	603-117-00-0	-

# 4. FIRST AID MEASURES

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

# In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eve contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

# **5. FIRE-FIGHTING MEASURES**

# Conditions of flammability

Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.

# Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

# Special protective equipment for fire-fighters

Wear self contained breathing apparatus for fire fighting if necessary.

# **Hazardous combustion products**

Hazardous decomposition products formed under fire conditions. - Carbon oxides

# **Further information**

Use water spray to cool unopened containers.

Sigma - 19516 Page 2 of 8

# **6. ACCIDENTAL RELEASE MEASURES**

# **Personal precautions**

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

# **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

# Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

# Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Handle and store under inert gas. Hygroscopic.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis	
2-Propanol	67-63-0	TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)	
Remarks	Eye & Upper Respiratory Tract irritation Central Nervous System impairment Not classifiable as a human carcinogen: Agents which cause concern that they could be carcinogenic for humans but which cannot be assessed conclusively because of a lack of data. In vitro or animal studies do not provide indications of carcinogenicity which are sufficient to classify the agent into one of the other categories.				
		STEL	400 ppm	USA. ACGIH Threshold Limit Values (TLV)	
	human carcinogen: Agents which cause concern that they could be carcinogenic for humans but which cannot be assessed conclusively because of a lack of data. In vitro or animal studies do not provide indications of carcinogenicity which are sufficient to classify the agent into one of the other categories.				
		TWA	400 ppm 980 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	
		STEL	500 ppm 1,225 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	
		TWA	400 ppm 980 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	
	The value in	The value in mg/m3 is approximate.			
		TWA	400 ppm 980 mg/m3	USA. NIOSH Recommended Exposure Limits	
		ST	500 ppm 1,225 mg/m3	USA. NIOSH Recommended Exposure Limits	

Sigma - 19516 Page 3 of 8

# Personal protective equipment

# Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

# Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

# Skin and body protection

impervious clothing, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

# Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# **Appearance**

Form liquid Colour colourless

Safety data

no data available pН

Meltina Melting point/range: -89.5 °C (-129.1 °F)

point/freezing point

Boiling point 82 °C (180 °F)

Flash point 12.0 °C (53.6 °F) - closed cup

Ignition temperature 425 °C (797 °F) 425.0 °C (797.0 °F) Autoignition

temperature

Lower explosion limit 2 %(V) 12.7 %(V) Upper explosion limit

43.2 hPa (32.4 mmHg) at 20.0 °C (68.0 °F) Vapour pressure

58.7 hPa (44.0 mmHg) at 25.0 °C (77.0 °F)

Density 0.785 g/mL at 25 °C (77 °F)

Water solubility completely soluble

Partition coefficient: n-octanol/water

log Pow: 0.05

Relative vapour

no data available

density

Odour alcohol-like

Odour Threshold no data available

Evaporation rate 3.0

Sigma - 19516 Page 4 of 8

# 10. STABILITY AND REACTIVITY

# **Chemical stability**

Stable under recommended storage conditions.

# Possibility of hazardous reactions

Vapours may form explosive mixture with air.

#### Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

# Materials to avoid

Oxidizing agents, Acid anhydrides, Aluminium, Halogenated compounds, Acids

# Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - no data available

# 11. TOXICOLOGICAL INFORMATION

# **Acute toxicity**

#### Oral LD50

LD50 Oral - rat - 5,045 mg/kg

Remarks: Behavioral:Altered sleep time (including change in righting reflex). Behavioral:Somnolence (general depressed activity).

#### Inhalation LC50

LC50 Inhalation - rat - 8 h - 16000 ppm

#### **Dermal LD50**

LD50 Dermal - rabbit - 12,800 mg/kg

# Other information on acute toxicity

no data available

#### Skin corrosion/irritation

Skin - rabbit - Mild skin irritation

# Serious eye damage/eye irritation

Eyes - rabbit - Eye irritation - 24 h

# Respiratory or skin sensitization

no data available

#### Germ cell mutagenicity

no data available

# Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (2-Propanol)

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or

anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by OSHA.

# Reproductive toxicity

Sigma - I9516 Page 5 of 8

no data available

# **Teratogenicity**

no data available

# Specific target organ toxicity - single exposure (Globally Harmonized System)

May cause drowsiness or dizziness.

# Specific target organ toxicity - repeated exposure (Globally Harmonized System)

no data available

# Aspiration hazard

no data available

#### Potential health effects

**Inhalation** May be harmful if inhaled. Causes respiratory tract irritation. Vapours may cause

drowsiness and dizziness.

**Ingestion** May be harmful if swallowed.

**Skin** May be harmful if absorbed through skin. Causes skin irritation.

**Eyes** Causes eye irritation.

# Signs and Symptoms of Exposure

Central nervous system depression, prolonged or repeated exposure can cause:, Nausea, Headache, Vomiting, narcosis, Drowsiness, Overexposure may cause mild, reversible liver effects.

# Synergistic effects

no data available

# **Additional Information**

RTECS: NT8050000

# 12. ECOLOGICAL INFORMATION

# **Toxicity**

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 9,640.00 mg/l - 96 h

Toxicity to daphnia and other aquatic invertebrates.

EC50 - Daphnia magna (Water flea) - 5,102.00 mg/l - 24 h

Immobilization EC50 - Daphnia magna (Water flea) - 6,851 mg/l - 24 h

Toxicity to algae EC50 - Desmodesmus subspicatus (green algae) - > 2,000.00 mg/l - 72 h

EC50 - Algae - > 1,000.00 mg/l - 24 h

# Persistence and degradability

no data available

# Bioaccumulative potential

no data available

# Mobility in soil

no data available

# PBT and vPvB assessment

no data available

# Other adverse effects

no data available

# 13. DISPOSAL CONSIDERATIONS

Sigma - I9516 Page 6 of 8

#### **Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

# Contaminated packaging

Dispose of as unused product.

# 14. TRANSPORT INFORMATION

DOT (US)

UN number: 1219 Class: 3 Packing group: II

Proper shipping name: Isopropanol

Marine pollutant: No

Poison Inhalation Hazard: No

**IMDG** 

Packing group: II EMS-No: F-E, S-D UN number: 1219 Class: 3

Proper shipping name: ISOPROPANOL

Marine pollutant: No

**IATA** 

UN number: 1219 Class: 3 Packing group: II

Proper shipping name: Isopropanol

# 15. REGULATORY INFORMATION

# **OSHA Hazards**

Flammable liquid, Target Organ Effect, Irritant

# **SARA 302 Components**

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

# **SARA 313 Components**

	CAS-NO.	Revision Date
2-Propanol	67-63-0	1987-01-01

CAC No

CAS-No.

Davisias Data

# SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

# **Massachusetts Right To Know Components**

	CAS-No.	Revision Date
2-Propanol	67-63-0	1987-01-01
Panneylyania Pight To Know Components		

# Pennsylvania Right To Know Components

-		CAS-No.	<b>Revision Date</b>
2-Propanol		67-63-0	1987-01-01

# **New Jersey Right To Know Components**

	CAS-No.	Revision Date
2-Propanol	67-63-0	1987-01-01

# California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

# 16. OTHER INFORMATION

# **Further information**

Copyright 2011 Sigma-Aldrich Co. License granted to make unlimited paper copies for internal use only.

Sigma - 19516 Page 7 of 8 The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Co., shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.

Sigma - 19516 Page 8 of 8